

## Prevention of stones from stains.

- Excellent surface sealer
- Protects porous stones
- Water based product
- Easy application



## Product Description

**weber aquaseal** is a polymer based sealer designed for protection of natural & synthetic stone. The unique formulation gives excellent water repellent as well as oleophobic i.e. oil repellent properties. It exhibits high resistance to oil & water stain on the surface treated with weber aqua seal. The treated pores of the surface form an invisible barrier allowing the vapour diffusion due to penetrating effect. It set to form hard wearing film while maintaining natural colour of stone & tile.

## Key Features

- Used for even low porous stone & marble
- Easy to apply using brush or cloth
- Water based system
- It can be applied for both external & internal application
- Highly durable & economical
- Superior coverage
- Seal & protect against stain of eatables

## Recommended Substrate

- Natural stones
- Synthetic marbles
- Sand stone
- Marbles Granites
- Travertine
- Concrete
- Fibrous cement material
- Bricks
- Unglazed tile
- Masonry
- Flamed, honed, finished granites & stones
- Pavers

### TECHNICAL PARAMETERS#

Appearance	Clear liquid
Density	1.02 + 0.02 gm/cc
pH	7 - 9

Test conditions at 27° C

## Directions for Use

### Application Methodology

- Surface should be clean, dry free of contamination eg, oil, dust, grease, laitance etc
- New surface need to dry for 48 - 72 hours before application of sealer
- Apply evenly weber aquaseal over surface with a paint brush, clean cloth or sponge. Care must be taken not to apply too thick or lumpy coats
- Allow it to penetrate for 5 - 20 minutes and wipe the surface with dry clean cloth or sponge after application. Any excess material needs to be wiped off
- Inter coat must be done wet on wet condition before first coat gets fully cured
- Allow 24 – 72 hours for air cure to develop hydrophobic & oleophobic effects
- Preliminary testing on small trial area is important to determine the compatibility & possible discoloration of the surface to be treated with weber aquaseal
- Do not apply on damp or wet surfaces; avoid application during wet weather conditions & on to surfaces that are extremely hot
- If applied on damp or wet surface are likely to peel or whitened in time
- Immediately clean tools & hand with water & soap after application

### Pack Size: 1 L & 20 L

### Consumption

Consumption: 3sqm – 35 sqm/lit, consumption may vary depending on the porosity level of the surface.

### Shelf Life

12 Months from the date of manufacturing, in a sealed condition.

### Storage

- Store in dry condition of normal ambient temperature
- Store out of direct sunlight
- To avoid any contamination closed the container after usage

#### Health & Safety:

- Keep away from children's reach
- Avoid contact with eyes, if enter eyes wash out with water & seek immediate medical attention
- Do not swallow, if swallowed seek immediate medical attention
- Use in well ventilated areas & away from source of ignition
- May cause minor skin irritation to sensitive skin. Wear gloves & mask during application

#### Note:

- Treated surface to be cleaned with normal water avoid acid & high pH based cleaners
- Surface need to retreated from time to time depends on its wear pattern i.e. types & frequency of traffic, weathering etc. to keep sealer at peak performance

**Disclaimer:** Information on this datasheet is to be treated as guideline for usage. Users are advised to undertake a trial for product suitability prior to it's full scale usage. There is no express or implied guaranty/warranty for the results. The company is not liable for any consequential damages.

**Marketed by: Saint-Gobain India Pvt. Ltd. – Weber business, Corporate Office:** 5<sup>th</sup> level, **Leela Business Park**, Andheri-Kurla Road, Andheri East, Mumbai – 400059 India.  
**Email:** weber-india@saint-gobain.com | **Website:** www.weber.co.in