



webertape stickon



Waterproofing tape for joints and corner treatments.



Product description

webertape stickon is a reinforced flexible 3 ply waterproofing tape designed to use for stanching or expansion joint, for vertical and horizontal corners of floors and walls. The product is recommended to be used in conjunction with waterproofing membrane like weberdry water-guard and weberdry PUA seal to prevent / fix leakage problem.

Typical application

- Construction or expansion joints.
- Treatment of dynamic cracks.
- Vertical and horizontal corners of floors and walls.
- Bathrooms, balconies, sumps and drains.
- Terraces and roofs.
- Swimming pools.

Features and benefits

- Excellent weatherability.
- High resistant to wear and tear.
- Strengthens joints and corners prone to cracks.

Mechanical properties

Property	Test standard	Value
Burst pressure max	Internal	2 bar
Breaking load longitudinal	DIN 527 – 3	104 N /15 mm
Breaking load lateral	DIN 527 – 3	23 N / 15 mm
Extension load longitudinal	DIN 527 – 3	70%
Extension load lateral	DIN 527 – 3	335%
Power absorption at 25% elasticity	DIN 527 – 3	0.341 N /mm
Power absorption at 50 % elasticity	DIN 527 – 3	0.34 N/mm
Resistance to water pressure	DIN EN 1928	> 1.5 bar
UV resistance	DIN EN ISO 4982-2	> 500 hours

- Superior chemical resistance to any acid or alkali.
- High resistance to water pressure.

Directions for use

- Clean the surface uniformly.
- Apply one coat of waterproofing membrane over the area to be treated.
- Apply webertape stickon over the surface while the waterproofing membrane is wet.
- Press webertape stickon with a squeeze to remove any voids or creases and wait for the waterproofing membrane to dry.
- Apply another coat of waterproofing membrane over webertape stickon covering the edges properly.

Physical properties

Colour	Grey
Width	120 mm
Thickness	~ 0.7 mm
Material weight	43 g / running mt
Working temperature range	-5 to 90 °C

Chemical properties

Acid	Resistance after 7 days of exposure at room temperature
3% Hydrochloric acid	Resistant
3% Sulphuric acid	Resistant
Citric acid 100 g/l	Resistant
Lactic acid 5%	Resistant
Potassium hydroxide 3% and 20%	Resistant
Sodium hypochlorite 0.3 g/l	Resistant
Salt water (20 g/l sea water salt)	Resistant

Precautions for use

Edges of webertape stickon must be uniformly topped with waterproofing membrane coat.

Pack size

25 mtr roll

Condition of Sale


Sold subject to the company's condition of sale which are available on request.

Caution

There may be irritation caused in eyes and skin in case of contact for a very long time. Wearing gloves is recommended while application. Please seek medical help if the problem persists for a long time.

Disclaimer

The user should determine the usability of the product for its intended use. Our products are manufactured under the Saint-Gobain quality standards, and subjected to strict quality control procedures. Since the company has no control over site conditions and installation procedures, the company will not be responsible under any circumstances for any loss, damage or liability from incorrect usage.



FDS / SDS / DoP
Product information



<https://goo.gl/d39avs>

Scan QR code to download android app for product information and technical data for our complete product range, directly from your smartphone.



Saint-Gobain India Pvt. Ltd. - Weber Business

5th Level, Leela Business Park, Andheri-Kurla Road, Andheri (East), Mumbai-400 059, Maharashtra. India.
Email: weber-india@saint-gobain.com Website : www.in.weber

